


Modular Patch Panels


45°
working
angle



LGX Style Adapter Plates



8 Port SC Simplex/LC Duplex Plate



8 Port ST Simplex/FC Simplex Plate



6 Port SC Duplex/LC Quad Plate



Blanking Plate

Our modular patch panel system in its basic form is supplied with the panels unloaded without adapter plates. The panel can also be pre-loaded with any 3 combination of adapter plates of your choice, or pre-loaded with pigtails to meet your project needs. An optional simple splice management kit can also be included. The tray is locked in place with two simple to operate plastic catches, when fully extended the tray is designed to lower to 45°, or move the tray to the side and it will lock to lower only 10°. This provides the perfect working platform for simple installation or easy maintenance and access even after the panel is installed in the rack.

Features/Benefits

- ▶ Recessed panel option
- ▶ Recessed adapters giving better bend radius
- ▶ Environmentally friendly materials & packaging
- ▶ No exposed screws
- ▶ Screen printed for easy labelling
- ▶ 45° working angle
- ▶ Multi functional rear cable entry options
- ▶ Panel number & rack number identification labels
- ▶ High quality finish, no sharp edges
- ▶ 4 cable entries (2XPG16, 2XPG13.5)
- ▶ Panels available in any color
- ▶ Private Label

Technical Characteristics

ELEMENT	CHARACTERISTIC
U Size	1U (44.4mm)
Width	482mm
Depth	205mm
Net weight	2.5kgs
Packaged weight	3kgs
Packaged Dimensions	450mm W X 55mm H x 260mm D
IP Rating	IP20
Suitable for adaptor type	LGX / MTP
Number of ports	3
Cable Entry 20mm	6
Mounting adjustment range	50mm
Material	Cold Rolled Steel
Material thickness	1.2mm
Material coating	Powder coating
Colour	Black RAL 9004
Operating Temperature	-40°C to + 50°C
Compliant to	RoHS, Reach / SVHC
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN 50173, IEC 60304, IEC 61754, EN 297-1